

Unit 1, 12 Kewdale Road, Welshpool WA 6106

Ph: 08 6350 1755 E:sales@sealsolutionsaustralia.com.au

CIRCULAR BELLOW SPECIFICATION SHEET

Date: 07/10/2008	Page: 5 Issue: 1	Revision: 5	Qty:	Cost Pe	r Unit: \$	
BELLOW WITH ZIPPER	Special Requirements		Phone:	Fax:		
	Material Type		- Address:			
6	Do You Want Clamps Supplied (Tick)	s No	- Email:			
INTERNAL BUSH SUPPORTS	Shaft Diameter	SD.	- Contact Name:			
	Cuff Length Required for Fastening	C2.	Company Name:			
	Inside Diameter of Cuff	B2.	-	ILO DAIL	•	
BELLOW WITH VENT	Cuff Length Required for Fastening	C1.	CUSTOMER DETA		:-	
	Inside Diameter of Cuff			Flange Connections, One End / Both Ends		
	Minimum Closed Length Excluding Cuffs A2.		☐ Double Stitch on Cuff Connections			
BELLOW WITH SUPPORT TAB	Maximum Extended Length Excluding Cuffs A1.		☐ Binder on Convolution Joins, Inside & Out			
	ORDERING SPECIFICATIONS Your Ref: Maximum Allowable Diameter of Convolutions O.D.		☐ Longitudinal Zipper; Straight or Spiral			
	A.2. CLOSED LENGTH.		☐ External Tie Straps for Vertical Application			
BELLOW WITH 4 TIE TABS	C.1 A.1. MAX EXTENDED LENGTH		☐ Internal Support Rings For Horizontal Application			
			SPECIAL FEATURES AVAILABLE ON REQUEST			
C	O.D. B2. SHAFT (S.D)	Min Max Average				
BELLOW WITH 2 TIE TABS	O.D. B.2. SHAFT (S.D.) B.1.		☐ Oil Type Working Temperature (In °C)			
			Chips Large	☐ Chips Small	☐ Coolant Type	
_ PLES	DOUBLE COLLARS DOUBLE FLANCES COLLAR-FLANCE COLLAR	R-EXT. FLANGE DOUBLE EXT. FLANGES SMOOTH SHAFT	☐ Abrasive Action	☐ Magnetic	□ Vacuum 	
PLAIN BELLOW	, www www www w		☐ Welding Splashes	☐ Saltwater	☐ Rust Action	
	.		☐ Dryness	☐ Heat	□ Dust / Sand	
A			☐ Indoor Use	Outdoor Use	☐ Humidity	